
7297 D


A range of corrosion proof fluorescent luminaires with three types of diffuser materials for aggressive environments


- A choice of T16 (T5) or T26 (T8) lamps
- All electrical components are mounted on a hinged and removable gear tray
- EPDM gasket between canopy and diffuser ensures IP67 seal
- Choice of distributions for enhanced optical performance. (Symmetrical or asymmetrical)



Las fotos, dibujos y datos técnicos de iluminación son únicamente imágenes simbólicas. Para obtener datos detallados de un producto, por favor, pulse sobre el producto deseado.







96005545

Material/ tipo

Canopy: glass reinforced polyester
Diffuser: clear, injection moulded acrylic (AC); clear, injection moulded impact-resistant polycarbonate (PC); opalized, injection moulded, chemical and impact resistant acrylic KEMSEG (KM)
Reflectors: aluminium

Instalación/ montaje

Ceiling, wall or catenary mounted. Adjustable brackets and catenary suspension as accessories.
Connection: cable entry through compression gland Ø22.5mm in each end. 2x5x2.5mm² terminal blocks with 3-phase through wiring. Stainless steel toggles clamp diffuser to canopy.

EN60598, SEMKO, IP67, Beam_Surface_2, Beam_Surface_3, SC1, CE, T26, 650

Los productos de Thorn Lighting están sujetos a un continuo desarrollo. Nos reservamos el derecho de planificar en nuestros productos sin publicaciones técnicas ni otras modicaciones formales.
© Thorn Lighting