



Quattro T5

Ultra shallow recessed modular T16 (T5) luminaires for exposed grid and concealed fix ceilings with choice of optic

- Shallow (58mm) square or rectangular body with plain white side panels
- Louvre and diffuser optics including very low glare louvre options for intensive or specialist VDU use
- Asymmetric louvre option for wall washing applications
- Versions with air handling functionality (30 l/s)



Las fotos, dibujos y datos técnicos de iluminación son únicamente imágenes simbólicas. Para obtener datos detallados de un producto, por favor, pulse sobre el producto deseado.



96211194

Material/ tipo

Body: white painted steel (close to RAL 9010)
 Side panels: white painted steel (perforated for air handling version)
 Louvre: aluminium
 Diffuser: PETG panel with white plastic frame

Instalación/ montaje

Suitable for most 15mm or 24mm exposed tee ceilings, the luminaire simply lays onto the ceiling grid for quick installation. For installation from below into concealed fixed and plasterboard ceilings, use mini-wedge brackets (supplied).
 UK: Electrical connection is via flush panel mounted GST 18/4 male connector (plug) for HF WL4 versions and 18/6 box T connector for HFD WL6 versions which protrudes 30mm from back of body. E3TX versions have an additional 18/3 box tee connector (not mains rated). Appropriate female connectors (sockets) must be ordered separately (see Thorn Connect range) to electrically connect with luminaires.